

RoHS2.0 compliant

REV	DATE	MODIFY

Features:

- * Used in ZH-A1271-H Series Housing
- * Accepts AWG #18+18 18+20 20+20 Wire Range
- * Insulation O.D.= 2.1~1.6 mm
- * Material : Phosphor Bronze or Brass
- * Finish : Gold-Plated or Tin-Plated
- * Qty/Reel : 5,000 PCS
- * Thickness: 0.25mm

Ordering information:

ZH-A1271-T X X X X L
1 2 3 4 5

- 1 T=Terminal
2 Plated:
T=Tin G=Gold H=Selective
3 Plated Method:
A: Plated before stamping
B: Stamping before plated
4 Material:
□BRASS
P:Phosphor bronze
5 L: 高脚

标示“”的尺寸需重点管控

TOLERANCE		 Zen High Precision Industrial Ltd.		
X.	--	TITLE 1.27mm (.050) Pitch SATA Power Cable Receptacle		
X.X	±0.20			
X.XX	±0.15			
X.XXX	±0.10			
ANGULAR	--			
APPROVALS		VIEW	SCALE	PART NO.
DRAWN	TOMA 25-OCT-2016		F	ZH-A1271-TXXXL
CHECKED		UNIT	SIZE	DWG NO.
APPROVED		MM	A4	T18-161025
				REV. AO
				SHEET 1 OF 1

